

# Safety Data Sheet

## AP-5200 Silicone



SDS Revision Date:

09/25/2015

### 1. Identification

#### 1.1. Product identifier

**Product Identity** AP-5200 Silicone

**Alternate Names** AP-5200 Silicone

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Intended use** For professional use only. See Technical Data Sheet.

**Application Method** See Technical Data Sheet.

#### 1.3. Details of the supplier of the safety data sheet

**Company Name** United Asphalt Company  
P.O Box 291  
Cedar Brook, NJ 08018

#### Emergency

**24 hour Emergency Telephone No.** 800-535-5053

**Customer Service: United Asphalt Company** 800-843-0317

### 2. Hazard(s) identification

#### 2.1. Classification of the substance or mixture

Flam. Liq. 3;H226	Flammable liquid and vapor.
Skin Irrit. 3;H316	Causes mild skin irritation. (Not adopted by US OSHA)
Eye Irrit. 2;H319	Causes serious eye irritation.
Skin Sens. 1;H317	May cause an allergic skin reaction.
Carc. 2;H351	Suspected of causing cancer.

#### 2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



**Warning**

H226 Flammable liquid and vapor.  
H316 Causes mild skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H351 Suspected of causing cancer.

**[Prevention]:**

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.  
P235 Keep cool.  
P240 Ground / bond container and receiving equipment.  
P241 Use explosion-proof electrical / ventilating / light / equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P261 Avoid breathing dust / fume / gas / mist / vapors / spray.  
P264 Wash thoroughly after handling.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P280 Wear protective gloves / eye protection / face protection.

**[Response]:**

P302+352 IF ON SKIN: Wash with plenty of soap and water.  
P303+361+353 IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.  
P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.  
P308+313 IF exposed or concerned: Get medical advice / attention.  
P321 Specific treatment (see information on this label).  
P333+313 If skin irritation or a rash occurs: Get medical advice / attention.  
P337+313 If eye irritation persists: Get medical advice / attention.  
P363 Wash contaminated clothing before reuse.  
P370+378 In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.

**[Storage]:**

P403+233 Store in a well ventilated place. Keep container tightly closed.  
P405 Store locked up.

**[Disposal]:**

P501 Dispose of contents / container in accordance with local / national regulations.

<b>3. Composition/information on ingredients</b>
--

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Petroleum distillates, hydrotreated light CAS Number: 0064742-47-8	10 - 25	Asp. Tox. 1;H304	[1]
Methyltris(methylethylketoximino)silane CAS Number: 0022984-54-9	1.0 - 10	Eye Irrit. 2;H319 Skin Irrit. 2;H315 Skin Sens. 1;H317	[1]
2-Butanone oxime CAS Number: 0000096-29-7	1.0 - 10	Carc. 2;H351 Acute Tox. 4;H312 Eye Dam. 1;H318 Skin Sens. 1;H317	[1]
Proprietary*	0.10 - 1.0	Skin Irrit. 2;H315 Eye Irrit. 2;H319 Skin Sens. 1;H317 Aquatic Chronic 3;H412	[1]

\*In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

## 4. First aid measures

### 4.1. Description of first aid measures

- General** In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
- Inhalation** Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
- Eyes** Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
- Skin** Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
- Ingestion** If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

### 4.2. Most important symptoms and effects, both acute and delayed

**Overview** Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness..

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 3 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure

See section 2 for further details.

<b>Eyes</b>	Causes serious eye irritation.
<b>Skin</b>	May cause an allergic skin reaction. Causes mild skin irritation. (Not adopted by US OSHA)

## 5. Fire-fighting measures

### 5.1. Extinguishing media

Foam, dry chemical, CO<sub>2</sub>, water

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: High temperatures and fires may produce carbon monoxide, oxides of nitrogen and various hydrocarbon fragments.

Keep away from heat / sparks / open flames / hot surfaces - No smoking.

Keep cool.

Ground / bond container and receiving equipment.

Use explosion-proof electrical / ventilating / light / equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust / fume / gas / mist / vapors / spray.

### 5.3. Advice for fire-fighters

If electrical equipment is involved, the use of foam should be avoided. Use water spray to cool non-involved containers.

Wear SCBA with a full-face piece operated in the positive pressure demand mode and full protective clothing (Bunker Gear) when fighting fires.

**ERG Guide No.** 127

## 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

### 6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

### 6.3. Methods and material for containment and cleaning up

Small spill: Remove with absorbent material.

Large spill: Eliminate all ignition sources. Ventilate enclosed areas or wear self-contained breathing apparatus. Recover free liquid in closed containers. Keep out of sewers and water courses. Clean area with absorbent material.

## 7. Handling and storage

### 7.1. Precautions for safe handling

Protect from freezing.

See section 2 for further details. - [Prevention]:

**7.2. Conditions for safe storage, including any incompatibilities**

Handle containers carefully to prevent damage and spillage.

Naked flames and smoking should not be permitted in storage areas. It is recommended that fork lift trucks and electrical equipment are protected to the appropriate standard.

Incompatible materials: Avoid strong oxidizing agents, concentrated nitric and sulfuric acids, halogen, and molten sulfur.

Store in a cool, dry place. Keep container tightly closed when not in use.

See section 2 for further details. - [Storage]:

**7.3. Specific end use(s)**

No data available.

**8. Exposure controls and personal protection**

**8.1. Control parameters**

**Exposure**

CAS No.	Ingredient	Source	Value
0064742-47-8	Petroleum distillates, hydrotreated light	Supplier	Recommended 300 ppm PEL

**8.2. Exposure controls**

**Respiratory**

If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.

**Eyes**

Not needed under normal circumstances.

**Skin**

Not needed under normal circumstances. Use protective gloves as needed to avoid skin irritation.

**Engineering Controls**

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.

**Other Work Practices**

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

**9. Physical and chemical properties**

<b>Appearance</b>	Viscous white or gray Liquid
<b>Odor</b>	petroleum odor
<b>Odor threshold</b>	Not Measured
<b>pH</b>	Not available
<b>Melting point / freezing point</b>	Not determined
<b>Initial boiling point and boiling range</b>	310 - 385°F
<b>Flash Point</b>	> 105°F TCC method
<b>Evaporation rate (Ether = 1)</b>	Slower than ether
<b>Flammability (solid, gas)</b>	Not Applicable
<b>Upper/lower flammability or explosive limits</b>	<b>Lower Explosive Limit:</b> 1.1 <b>Upper Explosive Limit:</b> 5.0
<b>Vapor pressure (Pa)</b>	Not determined
<b>Vapor Density</b>	Not available
<b>Specific Gravity</b>	1.23 (H2O = 1)
<b>Solubility in Water</b>	Negligible
<b>Partition coefficient n-octanol/water (Log Kow)</b>	Not Measured
<b>Auto-ignition temperature</b>	Not available
<b>Decomposition temperature</b>	Not available
<b>Viscosity</b>	4000 cps
<b>VOC Content</b>	< 250 g/liter
<b>Density</b>	Heavier than air (air + 1)

**9.2. Other information**

No other relevant information.

## 10. Stability and reactivity

**10.1. Reactivity**

Hazardous Polymerization will not occur.

**10.2. Chemical stability**

Stable under normal circumstances.

**10.3. Possibility of hazardous reactions**

No data available.

**10.4. Conditions to avoid**

Excessive heat and open flame.

**10.5. Incompatible materials**

Avoid strong oxidizing agents, concentrated nitric and sulfuric acids, halogen, and molten sulfur.

**10.6. Hazardous decomposition products**

High temperatures and fires may produce carbon monoxide, oxides of nitrogen and various hydrocarbon fragments.

## 11. Toxicological information

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Petroleum distillates, hydrotreated light - (64742-47-8)	> 5,000.00, Rat - Category: NA	No data available	No data available	No data available	No data available
Methyltris(methylethylketoximino)silane - (22984-54-9)	No data available	No data available	No data available	No data available	No data available
2-Butanone oxime - (96-29-7)	930.00, Rat - Category: 4	2,000.00, Rabbit - Category: 4	20.00, Rat - Category: 4	No data available	5,000.00, Rat - Category: 4
(Trimethoxysilylpropyl)ethylenediamine - (1760-24-3)	7,684.00, Rat - Category: NA	No data available	No data available	No data available	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

## 12. Ecological information

### 12.1. Toxicity

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and GHS and is not classified as dangerous for the environment, but contains substance(s) dangerous for the environment. See section 3 for details

### Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Quartz (non respirable) - (14808-60-7)	Not Available	Not Available	Not Available
Petroleum distillates, hydrotreated light - (64742-47-8)	45.00, Pimephales promelas	4,720.00, Dendronereides heteropoda	Not Available
2-Butanone oxime - (96-29-7)	320.00, Leuciscus idus	500.00, Daphnia magna	83.00 (72 hr), Scenedesmus subspicatus
(Trimethoxysilylpropyl)ethylenediamine - (1760-24-3)	597.00, Danio rerio	81.00, Daphnia magna	126.00 (72 hr), Scenedesmus subspicatus

### 12.2. Persistence and degradability

There is no data available on the preparation itself.

### 12.3. Bioaccumulative potential

Not Measured

### 12.4. Mobility in soil

No data available.

**12.5. Results of PBT and vPvB assessment**

This product contains no PBT/vPvB chemicals.

**12.6. Other adverse effects**

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Potentially toxic to aquatic life.

**13. Disposal considerations**

**13.1. Waste treatment methods**

Observe all federal, state and local regulations when disposing of this substance.

**14. Transport information**

	<b>DOT (Domestic Surface Transportation)</b>	<b>IMO / IMDG (Ocean Transportation)</b>	<b>ICAO/IATA</b>
<b>14.1. UN number</b>	Not Applicable	Not Regulated	Not Regulated
<b>14.2. UN proper shipping name</b>	Not Regulated	Not Regulated	Not Regulated
<b>14.3. Transport hazard class(es)</b>	<b>DOT Hazard Class:</b> Not Applicable	<b>IMDG:</b> Not Applicable <b>Sub Class:</b> Not Applicable	<b>Air Class:</b> Not Applicable
<b>14.4. Packing group</b>	Not Applicable	Not Applicable	Not Applicable
<b>14.5. Environmental hazards</b>			
<b>IMDG</b>	Marine Pollutant: No		
<b>14.6. Special precautions for user</b>	No further information		

**15. Regulatory information**

<b>Regulatory Overview</b>	The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.
<b>Toxic Substance Control Act ( TSCA)</b>	All components of this material are either listed or exempt from listing on the TSCA Inventory.
<b>WHMIS Classification</b>	B3 D2A
<b>US EPA Tier II Hazards</b>	<p style="text-align: right;"><b>Fire:</b> Yes</p> <p style="text-align: right;"><b>Sudden Release of Pressure:</b> No</p> <p style="text-align: right;"><b>Reactive:</b> No</p> <p style="text-align: right;"><b>Immediate (Acute):</b> Yes</p> <p style="text-align: right;"><b>Delayed (Chronic):</b> Yes</p>

**EPCRA 311/312 Chemicals and RQs:**  
To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**EPCRA 302 Extremely Hazardous:**  
To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.



**EPCRA 313 Toxic Chemicals:**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**California Proposition 65 - Carcinogens (>0.0%):**

This product may contain trace amounts of benzene, ethyl benzene and toluene which are known by the State of California to cause cancer, birth defects or other reproductive harm.

<b>16. Other information</b>
------------------------------

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

**This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.**

Judgments as to the suitability of information herein for the purchaser's purposes are necessarily the purchaser's responsibility. Although reasonable care has been taken in the preparation of such information, Aldo Products Company, extends no warranties, makes no representations, and assumes no responsibility as to the accuracy or suitability of such information for application to the purchaser's intended purpose or for consequences of its use.

End of Document