



**UNITED
ASPHALT**

MATERIAL SAFETY DATA SHEET

Page 1 of 3

HMIS RATING
HEALTH: 1
FLAMMABILITY: 0
REACTIVITY: 0

June 1, 2011

SECTION 1 – CHEMICAL PRODUCTS AND COMPANY IDENTIFICATION

IDENTITY: AP-1300 PRIMER/SEALER
C.A.S. Number: MIXTURE

MANUFACTURER:
UNITED ASPHALT COMPANY
PO BOX 291
CEDAR BROOK NJ 08018

PHONE # 856-753-9811
24 HR CHEMTRC EMERGENCY
800-424-9300

SECTION 2 – SOMPOSITION, INFORMATION ON INGREDIENTS

HAZARDOUS COMPONENTS	CAS#	OSHA PEL	WT%
NONE			

SECTION 3 – PHYSICAL CHEMICAL CHARACTERISTICS

BOILING RANGE: 212° F
VAPOR DENSITY: HEAVIER THAN AIR
COATING V.O.C. g/l: 0
SOLUBILITY IN WATER: COMPLETELY SOLUBLE
APPEARANCE AND ODOR: CLEAR
SPECIFIC GRAVITY: 1.04645
WEIGHT PER GAL: 8.6 POUNDS
SPECIFIC GRAVITY: 1.04645

SECTION 4 – FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 200 F
FLAMMABLE LIMITS IN AIR BY VOLUME – LOWER: N/A UPPER: N/A
EXTINGUISHING MEDIA: WATER
SPECIAL FIREFIGHTING PROCEDURES: Water may be used to cool closed containers, to prevent pressure build-up.
UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE

United Asphalt Company
237 North Grove Street Williamstown Junction, NJ 08009
PO Box 291 o Cedar Brook NJ 08018
856-753-9811 o 800-843-0317 o FAX: 856-753-9809
www.unitedasphalt.com

SECTION 5 – REACTIVITY DATA

STABILITY: STABLE

CONDITIONS TO AVOID: KEEP AWAY FROM ELEVATED TEMPERATURES

INCOMPATIBILITY: AVOID CONTACT WITH STRONG OXIDIZERS

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: N/A

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

SECTION 6 – HEALTH HAZARD DATA

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: Can cause dizziness, headaches, nausea, and possibly nose, throat and mucous membrane irritation.

SKIN AND EYE CONTACT HEALTH RISK AND SYMPTOMS OF EXPOSURE: None known.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: Drink 2 large glasses of water, **DO NOT** induces vomiting, call a physician.

HEALTH HAZARDS (ACUTE AND CHRONIC): ACUTE: Corrosive liquid – may cause burns to eye tissue with direct contact. CHRONIC: None known.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: None known.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: Remove to fresh air and rest.

SKIN: Immediately flush with running water.

EYE CONTACT: Immediately flush eyes with running water for at least 15 minutes. Seek medical attention immediately.

INGESTION: DO NOT INDUCE VOMITING! Drink 2 large glasses of water, call a physician.

SECTION 7 – PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Collect and reuse if possible. Wash area thoroughly with water.

WASTE DISPOSAL METHOD: Dispose in accordance with local, state, and federal regulations. If permitted by federal, state, and local regulations wash to sewer with large quantities of water.

SECTION 8 – PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

As required to prevent spillage. **Do not get in eyes, avoid exposure to skin.**

OTHER PRECAUTIONS: Keep closure tight and container upright to prevent leakage. Keep out of the reach of children.

SECTION 9 – CONTROL MEASURES

RESPIRATORY PROTECTION: If spray mists are generated, wear NIOSH approved particulate respirator.

VENTILATION: Use local exhaust if conditions exist that permit high vapor concentration.

PROTECTIVE GLOVES: Use chemical-resistant gloves when there could be direct contact.

EYE PROTECTION: Wear safety eyewear.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Use chemical –resistant apron on other impervious clothing to avoid contaminating regular clothing which could result in prolonged skin contact.

WORK/HYGIENIC PRACTICES: Wash thoroughly after use.

SECTION 10 – TRANSPORTATION DATA

US DOT CLASS PAINT, NOT REGULATED