

# Safety Data Sheet

## AP5400 HIGH SOLIDS SILICONE ROOF COATING

SDS Revision Date:

03/15/2019



### 1. Identification

#### 1.1. Product identifier

**Product Identity** AP-5400 High Solids Silicone Roof Coating  
**Alternate Names** Armour Proof AP-5400 High Solids Silicone Roof Coating

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Intended use** Silicone Coating  
**Application Method** See Technical Data Sheet.

#### 1.3. Details of the supplier of the safety data sheet

**Company Name** United Asphalt Company  
237 North Grove Street  
Berlin, NJ 08009

#### Emergency

**24 hour Emergency Telephone No.** 800-424-9300  
**Customer Service: United Asphalt Company, Inc.** 800-843-0317

### 2. Hazard(s) identification

#### 2.1. Classification of the substance or mixture

Flam. Liq. 4;H226	Combustible liquid.
Skin Irrit. 3;H316	Causes mild skin irritation. (Not adopted by US OSHA)
Eye Irrit. 2;H319	Causes serious eye irritation.
Skin Sens. 1;H317	May cause an allergic skin reaction.
Carc. 2;H351	Suspected of causing cancer.
Repr. 2;H361F	Suspected of damaging fertility.

#### 2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



**Danger**

H226 Combustible liquid.

# Safety Data Sheet

## AP5400 HIGH SOLIDS SILICONE ROOF COATING

SDS Revision Date:

03/15/2019



H316 Causes mild skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H351 Suspected of causing cancer.

H361f Suspected of damaging fertility.

### **[Prevention]:**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from flames / hot surfaces - No smoking.

P235 Keep cool.

P240 Ground / bond container and receiving equipment.

P241 Use explosion-proof electrical / ventilating / light / equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust / fume / gas / mist / vapors / spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves / eye protection / face protection.

### **[Response]:**

P302+352 IF ON SKIN: Wash with plenty of soap and water.

P303+361+353 IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P308+313 IF exposed or concerned: Get medical advice / attention.

P314 Get Medical advice / attention if you feel unwell.

P321 Specific treatment (see information on this label).

P333+313 If skin irritation or a rash occurs: Get medical advice / attention.

P337+313 If eye irritation persists: Get medical advice / attention.

P363 Wash contaminated clothing before reuse.

P370+378 In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.

### **[Storage]:**

P403+233 Store in a well ventilated place. Keep container tightly closed.

P405 Store locked up.

# Safety Data Sheet

## AP5400 HIGH SOLIDS SILICONE ROOF COATING

SDS Revision Date:

03/15/2019



### [Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

## 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Dimethylsiloxane CAS Number: 0063148-62-9	10 - 25	Aquatic Chronic 2;H411	[1]
Methyltris(methylethylketoximino)silane CAS Number: 0022984-54-9	1.0 - 10	Eye Irrit. 2;H319 Skin Irrit. 2;H315 Skin Sens. 1;H317	[1]
Titanium dioxide CAS Number: 0013463-67-7	1.0 - 10	Not Classified	[1][2]
Cristobalite CAS Number: 0014464-46-1	1.0 - 10	STOT RE 1;H372	[1]
2-Butanone oxime CAS Number: 0000096-29-7	1.0 - 10	Carc. 2;H351 Acute Tox. 4;H312 Eye Dam. 1;H318 Skin Sens. 1;H317	[1]
Proprietary*	0.10 - 1.0	Skin Irrit. 2;H315 Eye Irrit. 2;H319 Skin Sens. 1;H317 Aquatic Chronic 3;H412	[1]
Cyclotetrasiloxane, octamethyl- CAS Number: 0000556-67-2	0.10 - 1.0	Repr. 2;H361f Aquatic Chronic 4;H413	[1][3]

\*In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

\*The full texts of the phrases are shown in Section 16.

## 4. First aid measures

### 4.1. Description of first aid measures

#### General

In all cases of doubt, or when symptoms persist, seek medical attention.  
Never give anything by mouth to an unconscious person.

#### Inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.

#### Eyes

Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.

# Safety Data Sheet

## AP5400 HIGH SOLIDS SILICONE ROOF COATING

SDS Revision Date:

03/15/2019



**Skin** Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.

**Ingestion** If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

### 4.2. Most important symptoms and effects, both acute and delayed

**Overview** Effects of Overexposure  
Inhalation: Nasal and respiratory irritation, dizziness, fatigue, unconsciousness, asphyxiation.  
Ingestion: Can cause gastrointestinal disorders.  
Skin: Possible irritation, dermatitis, and defatting.  
  
Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 3 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure.  
See section 2 for further details.

**Eyes** Causes serious eye irritation.

**Skin** May cause an allergic skin reaction. Causes mild skin irritation. (

## 5. Fire-fighting measures

### 5.1. Extinguishing media

Water, carbon dioxide, foam or dry powder.

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: High temperatures and fires may produce carbon monoxide, oxides of nitrogen and various hydrocarbon fragments.

Keep away from heat / sparks / open flames / hot surfaces - No smoking.

Keep cool.

Ground / bond container and receiving equipment.

Use explosion-proof electrical / ventilating / light / equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust / fume / gas / mist / vapors / spray.

### 5.3. Advice for fire-fighters

This product is considered combustible and is a fire hazard. It supports combustion and decomposes under fire conditions to give off toxic materials. Do not pour, spill, or store near heat, spark sources, or open flame.

If electrical equipment is involved, the use of foam should be avoided. Use water spray to cool non-involved containers.

Wear SCBA with a full-face piece operated in the positive pressure demand mode and full protective clothing (Bunker Gear) when fighting fires.

**ERG Guide No.** ----

# Safety Data Sheet

## AP5400 HIGH SOLIDS SILICONE ROOF COATING

SDS Revision Date:

03/15/2019



### 6. Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

#### 6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

#### 6.3. Methods and material for containment and cleaning up

Small spill: Remove with absorbent material.

Large spill: Eliminate all ignition sources. Ventilate enclosed areas or wear self-contained breathing apparatus.

Recover free liquid in closed containers. Keep out of sewers and water courses. Clean area with absorbent material.

### 7. Handling and storage

#### 7.1. Precautions for safe handling

Protect from freezing.

See section 2 for further details. - [Prevention]:

#### 7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Naked flames and smoking should not be permitted in storage areas. It is recommended that fork lift trucks and electrical equipment are protected to the appropriate standard.

Incompatible materials: Avoid strong oxidizing agents, concentrated nitric and sulfuric acids, halogen, and molten sulfur.

Store in a cool, dry place. Keep container tightly closed when not in use.

See section 2 for further details. - [Storage]:

#### 7.3. Specific end use(s)

No data available.

### 8. Exposure controls and personal protection

#### 8.1. Control parameters

##### Exposure

CAS No.	Ingredient	Source	Value
0014464-46-1	Cristobalite	ACGIH	TWA: 0.025 mg/m <sup>3</sup>

#### 8.2. Exposure controls

# Safety Data Sheet

## AP5400 HIGH SOLIDS SILICONE ROOF COATING

SDS Revision Date:

03/15/2019



<b>Respiratory</b>	If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.
<b>Eyes</b>	Not normally required.
<b>Skin</b>	Use protective gloves as needed to avoid skin irritation.
<b>Engineering Controls</b>	Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.
<b>Other Work Practices</b>	Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

### 9. Physical and chemical properties

<b>Appearance</b>	Viscous white or gray Liquid
<b>Odor</b>	Not specified
<b>Odor threshold</b>	Not determined
<b>pH</b>	Not available
<b>Melting point / freezing point</b>	Not determined
<b>Initial boiling point and boiling range</b>	Not determined
<b>Flash Point</b>	160°F ASTM D93
<b>Evaporation rate (Ether = 1)</b>	Slower than ether
<b>Flammability (solid, gas)</b>	Not Applicable
<b>Upper/lower flammability or explosive limits</b>	<b>Lower Explosive Limit: 1.1</b> <b>Upper Explosive Limit: 5.0</b>
<b>Vapor pressure (Pa)</b>	Not determined
<b>Vapor Density</b>	Not available
<b>Specific Gravity</b>	1.37 (H <sub>2</sub> O = 1)
<b>Solubility in Water</b>	Negligible
<b>Partition coefficient n-octanol/water (Log Kow)</b>	Not Measured
<b>Auto-ignition temperature</b>	Not available
<b>Decomposition temperature</b>	Not available
<b>Viscosity (cSt)</b>	Not available
<b>VOC Content</b>	< 50 g/liter
<b>Density</b>	Heavier than air (Air + 1)

#### 9.2. Other information

No other relevant information.

# Safety Data Sheet

## AP5400 HIGH SOLIDS SILICONE ROOF COATING

SDS Revision Date:

03/15/2019



### 10. Stability and reactivity

**10.1. Reactivity**

Hazardous Polymerization will not occur.

**10.2. Chemical stability**

Stable under normal circumstances.

**10.3. Possibility of hazardous reactions**

No data available.

**10.4. Conditions to avoid**

Keep away from heat, flame and other potential ignition sources.

**10.5. Incompatible materials**

Avoid strong oxidizing agents, concentrated nitric and sulfuric acids, halogen, and molten sulfur.

**10.6. Hazardous decomposition products**

High temperatures and fires may produce carbon monoxide, oxides of nitrogen and various hydrocarbon fragments.

### 11. Toxicological information

**Acute toxicity**

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
2-Butanone oxime - (96-29-7)	930.00, Rat - Category: 4	2,000.00, Rabbit - Category: 4	20.00, Rat - Category: 4	No data available	5,000.00, Rat - Category: 4
Cyclotetrasiloxane, octamethyl- - (556-67-2)	2,000.00, Rat - Category: 4	4,640.00, Rabbit - Category: 5	36.00, Rat - Category: NA	No data available	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

**Carcinogen Data**

CAS No.	Ingredient	Source	Value
0013463-67-7	Titanium dioxide	IARC	Group 2b: Yes
0014464-46-1	Cristobalite	NTP	Known: Yes

### 12. Ecological information

**12.1. Toxicity**

# Safety Data Sheet

## AP5400 HIGH SOLIDS SILICONE ROOF COATING

SDS Revision Date:

03/15/2019



The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and GHS and is not classified as dangerous for the environment, but contains substance(s) dangerous for the environment. See section 3 for details

### Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Dimethylsiloxane - (63148-62-9)	3.16, Ictalurus punctatus	44.50, Daphnia magna	Not Available
2-Butanone oxime - (96-29-7)	320.00, Leuciscus idus	500.00, Daphnia magna	83.00 (72 hr), Scenedesmus subspicatus
Proprietary	597.00, Danio rerio	81.00, Daphnia magna	126.00 (72 hr), Scenedesmus subspicatus
Cyclotetrasiloxane, octamethyl- - (556-67-2)	200.00, Leuciscus idus	25.20, Daphnia magna	Not Available

### 12.2. Persistence and degradability

There is no data available on the preparation itself.

### 12.3. Bioaccumulative potential

Not Measured

### 12.4. Mobility in soil

No data available.

### 12.5. Results of PBT and vPvB assessment

This product contains PBT/vPvB chemicals.

### 12.6. Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Potentially toxic to aquatic life.

## 13. Disposal considerations

### 13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

## 14. Transport information

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
14.1. UN number	Not Applicable	Not Regulated	Not Regulated
14.2. UN proper shipping name	Not Regulated	Not Regulated	Not Regulated



# Safety Data Sheet

## AP5400 HIGH SOLIDS SILICONE ROOF COATING

SDS Revision Date:

03/15/2019



<b>14.3. Transport hazard class(es)</b>	<b>DOT Hazard Class:</b> Not Applicable	<b>IMDG:</b> Not Applicable <b>Sub Class:</b> Not Applicable	<b>Air Class:</b> Not Applicable
<b>14.4. Packing group</b>	Not Applicable	Not Applicable	Not Applicable
<b>14.5. Environmental hazards</b>			
<b>IMDG</b>	Marine Pollutant: No		
<b>14.6. Special precautions for user</b>			
No further information			

### 15. Regulatory information

<b>Regulatory Overview</b>	The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.
<b>Toxic Substance Control Act ( TSCA)</b>	All components of this material are either listed or exempt from listing on the TSCA Inventory.
<b>WHMIS Classification</b>	B3 D2A
<b>US EPA Tier II Hazards</b>	<b>Fire:</b> Yes <b>Sudden Release of Pressure:</b> No <b>Reactive:</b> No <b>Immediate (Acute):</b> Yes <b>Delayed (Chronic):</b> Yes

#### EPCRA 311/312 Chemicals and RQs:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

#### EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

#### EPCRA 313 Toxic Chemicals:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

#### Proposition 65 - Carcinogens (>0.0%):

Titanium dioxide

#### Proposition 65 - Developmental Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

#### Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

#### Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

#### New Jersey RTK Substances (>1%):

Cristobalite

Titanium dioxide

#### Pennsylvania RTK Substances (>1%):

# Safety Data Sheet

## AP5400 HIGH SOLIDS SILICONE ROOF COATING

SDS Revision Date:

03/15/2019



Cristobalite  
Titanium dioxide

### 16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

**This is the latest version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.**

Judgments as to the suitability of information herein for the purchaser's purposes are necessarily the purchaser's responsibility. Although reasonable care has been taken in the preparation of such information, United Asphalt Company Inc., extends no warranties, makes no representations, and assumes no responsibility as to the accuracy or suitability of such information for application to the purchaser's intended purpose or for consequences of its use.

End of Document